



Your Single Source For Innovative
Architectural Concrete Solutions

BOMANITE RELEASE AGENT

Technical Bulletin

Bomanite Release Agent is a dry blend of chemical powders and color pigments designed for use in the Bomacron process to allow the clean release of Bomacron texturing tools from the concrete surface. In addition to providing a clean release, it also adds color variation to the textured surface, thus providing the attractive two-color look which is part of most Bomacron installations. Bomanite Release Agent is applied by specially licensed, trained and equipped Bomanite licensees.

FEATURES AND BENEFITS:

- ***Provides Excellent release for texturing tools***
- ***Provides color variation and additional highlights in the textured surface of Bomacron***

GENERAL INFORMATION:

Coverage Guidelines

All Colors 700 -1,000 sq. ft. per 20 lb. unit/65-93 sq. m. per 9.1 kg. unit

Packaging

Pail or Bag 20 pounds/9.1 kilograms

Colors

60 standard colors – Refer to Bomanite Standard Color Chart for color selections and names. Custom colors available upon request (minimum 1,000 sq. ft.).

Maintenance

All Bomanite/Bomacron installations should be regularly maintained by a licensed Bomanite contractor in order to maintain a top quality appearance. Every 18 to 36 months, installations should be inspected by your local Bomanite contractor and cleaned and resealed as required by volume and intensity of traffic. Contact your local Bomanite contractor for the proper maintenance program in your area, as the need for maintenance will vary depending on a number of factors including traffic conditions, geographical location and weather.

Caution

Use face mask or respirator. Do not allow to get into eyes. Keep out of the reach of children. Prolonged breathing will cause throat and lung irritation. See Material Safety Data Sheet for complete information.

Warranty

This product is warranted to be of uniform quality within manufacturing tolerances. Since control is not exercised over its use, no warranty, expressed or implied, is made as to the effects of such use. Seller and manufacturer obligations under this warranty shall be limited to refunding the purchase price of that portion of the material proven to be defective. The user assumes all other risks and liabilities resulting from use of this product.

Additional product information, technical bulletins and specifications are available online at www.bomanite.com or through one of our Bomanite Licensed Contractors. For additional assistance with specifications or technical issues, contact The Bomanite Company.